

Impran

Stone impregnator

- ▲ Penetrates deep into the pores, fast-drying and tread-proof afterwards
- ▲ Long-lasting protection for the treated stone surfaces
- ▲ Reduces salt efflorescences, moss and algae growth, mould formation and damage caused by weather and frost
- ▲ Does not affect the steam permeability of the stone
- ▲ Alkali and UV-resistant
- ▲ Hydrophobic and oleophobic effect
- ▲ Fully hardened after approx. 48 hours
- ▲ Free from aromatic hydrocarbons
- ▲ Report to DIN 51130 confirming slip-resistance rating R9 available



Area of application

For the impregnation of natural stone, artificial stone and ceramic floors with porous or absorbent surfaces, e.g. porcelain tiles, marble and granite. Can be used indoors and outdoors.

Application

Please test on a small inconspicuous spot before first application. Check for colour changes and colour depth. Ventilate rooms well during and after use. The floor and product temperature must be between 5 °C and 25 °C.

Preparation of the surface:

Surfaces must be free from wax and grease. Only use product on thoroughly cleaned stone surfaces.

Impregnation:

Depending on the absorbency of the surface, 1–4 layers at intervals of approx. 30 minutes.

Apply the undiluted product to the surface and spread thinly and evenly with a mop. Excess product that has not penetrated into the floor after 15 minutes must be thoroughly and completely removed from the surface using a squeegee. Remove product residue by wiping with a dry mop. Product residue that remains on the surface forms a sticky residue once that cannot be removed anymore once hardened. Consumption: 5.0–500.0 ml/m².

Consumption depends on the absorbency of the stone surface.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Do not smoke!

Ingredients

Water-insoluble solvents, impregnation agents.

Classification

Classification (in concentrate): GHS02, GHS07, GHS08, Danger. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. P271 Use only outdoors or in a well-ventilated area. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P370+P378 In case of fire: Use extinguishing powder to extinguish. EUH066 Repeated exposure may cause skin dryness or cracking. Contains: C10-12 Alkane/Cycloalkane (INCI)

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j210465	Carton of 4 x 2.5 L tin canisters	54