

# Kiehl-PurOil

## Water-based impregnating maintenance oil

- ▲ Emphasises the colouring depending on the type of floor
- ▲ Oxidation hardening and vapour diffusion
- ▲ Free from heavy metals, solvents, formaldehyde and fragrances
- ▲ Easy to use
- ▲ High filling capacity



### Area of application

For initial and re-oiling of real wood surfaces as well as natural and artificial stone. Do not use on sealed, coated or waxed surfaces.

### Application

Please test on a small inconspicuous spot before first application. The surfaces must be clean, release-agent free and properly prepared to ensure faultless adhesion and appearance. Shake well before use. Floor and product temperature must be between 15 °C and 25 °C. Avoid draughts during use and drying. Ventilate rooms properly after drying.

#### Preparation of the surface:

Dry clean parquet surfaces before coating (use Kiehl-Legno Pad). Accruing dust must be removed. Wet stripping must be carried out on stone surfaces.

#### Initial oiling (impregnating):

Detailed instructions are available on request.

#### Re-oiling (impregnating):

Depending on the absorbency of the surface, 1–2 layers at intervals of approx. 2 hours.

After preparing the surfaces, apply a thin coat of undiluted product to the clean floor using a flat mop or waxer. Safe to walk on after approx. 2 hours and wipe-proof after approx. 24 hours. Consumption: 25.0–50.0 ml/m<sup>2</sup> per application.

#### Spray buffing:

Use product undiluted.

Apply using a spray bottle and single disc machine (approx. 150 rpm). Safe to walk on after approx. 2 hours and wipe-proof after approx. 24 hours. Consumption: 5.0 ml/m<sup>2</sup>.

Clean tools with water.



### Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Protect from frost. Keep out of the reach of children. Not suitable for paint spraying. Use P2 dust filter for grinding. When using do not eat, drink or smoke. In case of contact with eyes or skin, immediately and thoroughly rinse with water. Ensure good ventilation during use and drying. Clean utensils immediately after use with soap and water. Do not empty into drains, aquatic environment or earth. Make sure that containers are completely empty for recycling. Liquid paint leftovers should be returned to a collection facility for paint residues. Packaging material is recyclable.

### Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, drying agents, vegetal oil components, preservatives (Benz-, Methyl-, Methylchloroisothiazolinone). pH value (concentrate): approx. 8

Art. No.

j221905

Packaging unit (PU)

Carton of 2 x 5 L canisters

Numbers of PU per pallet

56

# Kiehl-PurOil

## Water-based impregnating maintenance oil

---

### Classification

Classification (in concentrate): EUH208 Contains Benz-, Methyl-, Methylchloroisothiazolinone. May produce an allergic reaction.